



40' Gooseneck ISO Container Chassis



STANDARD PRODUCT FEATURES

- Designed for standard 40' ISO Container
- Heavy duty steel "I" main beams
- 2 speed landing gear
- 10 x 20 bias ply tube type tires
- 20" cast steel spoke wheels
- 12V electrical system
- Anti-sail mud flaps
- (4) Heavy duty twistlocks
- Heavy duty sand shoes
- "Hutch" suspension
- ABS system
- Zinc rich primer
- Black, polyurethane top coat
- AAR, DOT, ANSI, TOFC, FM, USS, ISO, SAE & TTMA APPROVALS
- The chassis frame and main fabricated parts are of high strength low alloy steel ASTM A572 Grade 50, having a minimum yield point of 50,000 PSI

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	LENGTH	HEIGHT (Front GN)	HEIGHT (Rear MB)	WIDTH
Ft in	40'	4' 5"	4'	8'
Metric	12,192	1,372	1,219	2,438

	Tare Weight	Payload	Gross Weight
Lb	6,600	67,200	74,000
Metric	2,994	30,482	33,566

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

321 Valley Rd. Suite A, Hillsborough, NJ 08844 | Phone: 908 . 371 . 1790 | Email: info@coldstorage2go.com

www.coldstorage2go.com/ | © Copyright 2022, Cold Storage 2 Go

SB483
40' Gooseneck
ISO Container Chassis

• 040422-R00