



40' X 8' 6" Insulated ISO Cargo Container with Climate Control

SB531-6-CC
40' X 8' 6" Insulated ISO Cargo Container with Climate Control



STANDARD PRODUCT FEATURES

- Full opening swing cargo doors on (1) end
- Aluminum T-grade floors
- 3" thick foam insulation including the floor
- Heavy gauge plastic or stainless steel interior lining
- BARD wall mounted heat pump with dehumidification
- 2-ton cooling with 4 kw heat
- 230/208 volts, single phase, 60 amps
- Temperature range +65F to +75F
- Dehumidify to 45%
- Thermostat/de-humidistat
- Three interior lights with switch
- Watertight exterior circuit breaker panel
- 50' power cable



110518-R01

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD FOR NINE (9) HIGH STACKING

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	40' 0"	38' 0"	8' 6"	7' 3 5/8"	8' 0"	7' 5 5/8"	7' 6 1/2"	7' 5 5/8"
Metric	12,192	11,582	2,591	2,226	2,438	2,276	2,299	2,276
	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		CUBIC CAPACITY	
Lbs	8,300		59,990		67,200		2,139 Cu. Ft.	
Kgs	3,765		27,210		30,480		60.6 Cu. M.	

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

ISO 9001



CERTIFIED QUALITY
MANAGEMENT SYSTEM